

PVC UNREINFORCED AIR & WATER TUBE

SKU / PART NUMBER: PCT

Application: Fluids, Gases, Powders and Granules

Reinforcement: None

Temperature Rated: -15°C to +60°C

Material: PVC



Clear unreinforced PVC hose has excellent flexibility and transparency and is suitable for conveyance of fluids, gases, powders and granules at low pressure at temperatures. The tubing has good abrasion and corrosion resistance, resistant to dilute acids and alkalis and features a smooth bore (seamless) for optimal flow rates. The clear wall makes it easier to view the liquid inside the tubes, which can help detect kinks and the incorrect transfer of liquids through certain lines.

Inside Diameter	Outside Diameter	Working Pressure	Working Pressure	Maximum Coil
3mm	5mm	2 Bar	29 PSI	100 Metres
4mm	6mm	2 Bar	29 PSI	100 Metres
5mm	8mm	2 Bar	29 PSI	100 Metres
6mm	8mm	2 Bar	29 PSI	100 Metres
8mm	11mm	1.5 Bar	22 PSI	100 Metres
9.5mm	12mm	1.5 Bar	22 PSI	100 Metres
10mm	13mm	1.5 Bar	22 PSI	100 Metres
12mm	15mm	1.5 Bar	22 PSI	100 Metres
16mm	19mm	1 Bar	15 PSI	50 Metres
19mm	22mm	1 Bar	15 PSI	50 Metres
22mm	26mm	1.5 Bar	22 PSI	50 Metres
25mm	29mm	1.5 Bar	22 PSI	50 Metres

Tel : 01924 496111

Web: autosiliconehoses.com

Email: web@autosiliconehoses.com

Google: [Find us on Google](#)