

RUBBER LPG GAS PROPANE HOSE ISO3821

SKU / PART NUMBER: RLH

Application: LPG & Propane Gas Hose

Reinforcement: High Tensile Textile

Temperature Rated: -30°C to +80°C

Standard: BS EN559, BS 3212/2, BS 5120, BS EN1763, ISO3821



LPG Gas Hose to suit virtually every application. Low pressure is approved and conforms to BS3212-1 while the high pressure gas hose is approved and conforms to BS3212-2.

Inside Diameter	Outside Diameter	Working Pressure	Working Pressure	Bend Radius	Maximum Length
5mm	12mm	20 Bar	300 PSI	60mm	100 Metres
6mm	14mm	20 Bar	300 PSI	60mm	100 Metres
8mm	16mm	20 Bar	300 PSI	80mm	100 Metres
10mm	18mm	20 Bar	300 PSI	100mm	100 Metres
13mm	22mm	20 Bar	300 PSI	130mm	100 Metres
19mm	28mm	20 Bar	300 PSI	200mm	100 Metres

Tel : 01924 496111

Web: autosiliconehoses.com

Email: web@autosiliconehoses.com

Google: [Find us on Google](#)

Unit 3 Holmebank Mills, Station Road, Mirfield, West Yorkshire, WF14 8NA - [Find us on Google Maps](#)
AP Motor Store Limited - VAT No. GB334646006 - Reg No. 09188175