

# RUBBER MARINE FUEL & OIL HOSE ISO7840

SKU / PART NUMBER: RMH

**Application:** Diesel & Petrol Marine Fuel Delivery

**Reinforcement:** Synthetic Yarn / A2 Wire Helix

**Temperature Rated:** -35°C to +100°C

**Standard:** ISO7840 Type A1 / A2



Rubber marine fuel hose is suitable for delivery of diesel and petrol marine fuel. The tube is composed of a black nitrile rubber, with a smooth black chloroprene rubber cover. High tensile polyester fibres are weaved between the layers to provide the hose with reinforcement. Sizes above 19mm also have an embedded steel wire helix reinforcement.

Our marine hose is abrasion, ozone, weather, heat and oil resistant, also resistant to flame and sea conditions. ISO 7840 Type A1 (5mm > 19mm), ISO 7840 Type A2 (25mm > 51mm)

Diesel & Petrol Marine Fuel Delivery Hoses.

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Busting Pressure	Bend Radius
5mm	12mm	3.5mm	10 Bar	30 Bar	50mm
6mm	13mm	3.5mm	10 Bar	30 Bar	60mm
8mm	15mm	3.5mm	10 Bar	30 Bar	80mm
10mm	17mm	3.5mm	10 Bar	30 Bar	100mm
13mm	21mm	4mm	10 Bar	30 Bar	130mm
16mm	25mm	4.5mm	10 Bar	30 Bar	160mm
19mm	29mm	5mm	10 Bar	30 Bar	190mm
25mm	35mm	5mm	5 Bar	15 Bar	152mm
32mm	42mm	5mm	5 Bar	15 Bar	192mm
38mm	48mm	5mm	5 Bar	15 Bar	228mm
51mm	63mm	6mm	5 Bar	15 Bar	305mm

Tel : 01924 496111

Web: [autosiliconehoses.com](http://autosiliconehoses.com)

Email: [web@autosiliconehoses.com](mailto:web@autosiliconehoses.com)

Google: [Find us on Google](#)