## **RUBBER STAINLESS STEEL BRAIDED FUEL HOSE**

SKU / PART NUMBER: RSO

Application: Fuel / Oil / Water / Air Reinforcement: Stainless Steel 304 Braid Outer Temperature Rated: -30°C to +100°C Standard: BS 5118/2



Stainless steel braided high performance racing hose to meet any plumbing need for all kind of car, truck and boat. Flexible and durable with maximum pressure capability, manufactured with precision to provide superior fluid handling.

This fuel hose features a stainless steel outer braiding which not only looks good, it also protects the hose from heat and abrasion damage. For use with either swaged unions, push-on fittings or standard hose clips NBR fuel and oil rubber inner hose with a textile reinforcement make this hose perfect for commercial fuel and oil mixtures.

Nitrile Rubber Inner - Stainless Steel 304 Braid Outer

| Inside Diameter | Outside Diameter | Working Pressure | Bursting Pressure | Maximum Coil |
|-----------------|------------------|------------------|-------------------|--------------|
| 6mm             | 11mm             | 20 Bar           | 60 Bar            | 50 Metres    |
| 8mm             | 13mm             | 20 Bar           | 60 Bar            | 50 Metres    |
| 10mm            | 17mm             | 20 Bar           | 60 Bar            | 50 Metres    |
| 13mm            |                  | 20 Bar           | 60 Bar            | 50 Metres    |

Tel: 01924 496111
Web: autosiliconehoses.com
Email: web@autosiliconehoses.com
Google: Find us on Google

Unit 3 Holmebank Mills, Station Road, Mirfield, West Yorkshire, WF14 8NA - <u>Find us on Google Maps</u> AP Motor Store Limited - VAT No. GB334646006 - Reg No. 09188175