RUBBER FLEXIBLE WIRE RADIATOR HOSE SAEJ20R3

SKU / PART NUMBER: RWR

**Application:** Radiator / Coolant / Hot Water Hose **Reinforcement:** Wire Helix / Synthetic Textile

Temperature Rated: -40°C to +120°C

Standard: SAEJ20R3



Rubber wire reinforced hose is a highly flexible EPDM rubber hose with an embedded steel wire helix and textile braid reinforcement. The hose is very flexible and strong making it ideal for applications such as in vehicle heating and cooling systems.

The black EPDM rubber resistant to many mild chemicals, glycol based anti-freeze solutions and most corrosion inhibitors and has good heat, abrasion and ozone resistance.

Smooth Rubber EPDM Inner - Steel Wire Helix & Textile Braid Reinforcement - Wrapped EPDM Outer Outer appearance is either smooth or convoluted dependent upon stock at time of ordering.

Inside Diameter	Outside Diameter	Working Pressure	Bursting Pressure	Maximum Coil
13mm	21mm	10 Bar	30 Bar	20 Metres
16mm	24mm	10 Bar	30 Bar	20 Metres
19mm	27mm	10 Bar	30 Bar	20 Metres
22mm	30mm	10 Bar	30 Bar	20 Metres
25mm	34mm	10 Bar	30 Bar	20 Metres
28mm	36mm	10 Bar	30 Bar	20 Metres
32mm	41mm	10 Bar	30 Bar	20 Metres
35mm	45mm	10 Bar	30 Bar	20 Metres
38mm	47mm	10 Bar	30 Bar	20 Metres
45mm	55mm	10 Bar	30 Bar	20 Metres
51mm	61mm	10 Bar	30 Bar	20 Metres

Tel: 01924 496111

✓ Web: <u>autosiliconehoses.com</u>

✓ Email: web@autosiliconehoses.com

Google: Find us on Google