

PU POLYURETHANE DUCTING – FLEXIBLE HOSE

SKU / PART NUMBER: PUD

Application: Woodworking, Dust Relocation & Air Extraction

Reinforcement: Steel Wire Helix

Temperature Rated: -40°C to +90°C

Wall Thickness: 0.4mm

Material: Corrugated Polyurethane

Colour: Translucent



Polyurethane, often abbreviated as PU, PUR, or even TPU (Thermoplastic polyurethane), combines the best properties of plastic and rubber.

Ideally suited for dry applications only, the suction and transfer of dust, chips and abrasive particles such as wood waste and general industrial and agricultural applications.

Internal Diameter	Outside Diameter	Pressure Rating	Vacuum Rating	Weight
50mm	58mm	0.49 Bar	0.25 Bar	0.25 kg/m
65mm	73mm	0.38 Bar	0.18 Bar	0.36 kg/m
80mm	92mm	0.30 Bar	0.12 Bar	0.47 kg/m
100mm	106mm	0.25 Bar	0.08 Bar	0.51 kg/m

Tel : 01924 496111

Web: autosiliconehoses.com

Email: web@autosiliconehoses.com

Google: [Find us on Google](#)

Unit 3 Holmebank Mills, Station Road, Mirfield, West Yorkshire, WF14 8NA - [Find us on Google Maps](#)
AP Motor Store Limited - VAT No. GB334646006 - Reg No. 09188175