

RUBBER FUEL/OIL HOSE BSAU108/2 – SAE J30R6

SKU / PART NUMBER: RPH

Application: Radiator, Fuel Hose, Oil & Air Hose

Reinforcement: High Tensile Synthetic

Temperature Rated: -40°C to +120°C

Standard: BSAU108/2, SAE J30R6

Cover: EPDM Rubber



This premium quality multi purpose hose is fully compliant with the international BSAU108/2 and SAE J30R6 specifications for fuel hose, and is suitable for the conveyance of petroleum products with up to 50% aromatic content, including unleaded petrol.

Rubber NBR material is specially designed for automotive and engine applications. The hose is suitable for petrol, diesel, ethanol, gasoline and is very flexible for easy routing. The smooth outer is resistant to oils and fuels, heat, ozone and weather.

Inside Diameter	Outside Diameter	Working Pressure	Bursting Pressure	Maximum Coil
5mm	12mm	20 Bar	60 Bar	100 Metres
6mm	13mm	20 Bar	60 Bar	100 Metres
8mm	15mm	20 Bar	60 Bar	100 Metres
10mm	17mm	20 Bar	60 Bar	100 Metres
13mm	21mm	20 Bar	60 Bar	100 Metres
16mm	25mm	20 Bar	60 Bar	100 Metres
19mm	29mm	20 Bar	60 Bar	100 Metres
22mm	32mm	20 Bar	60 Bar	100 Metres
25mm	36mm	20 Bar	60 Bar	100 Metres

Tel : 01924 496111

Web: autosiliconehoses.com

Email: web@autosiliconehoses.com

Google: [Find us on Google](#)